

AMENDMENTS TO THE CLAIMS

The claims in this listing will replace all prior versions, and listings, of claims in the application.

1. (Currently Amended): An image transmitting apparatus for transmitting image data to an image receiving apparatus to which a changeable IP address is assigned by an external apparatus according to first and second modes, the image transmitting apparatus comprising:

a memory that stores a table including a fixed address of the image receiving apparatus, the fixed address comprising a MAC (Media Access Control) address, and being stored in association with a destination mail address;

a processor configured to obtain the current IP address of the image receiving apparatus by use of the fixed address stored in the memory;

an inputter for inputting the destination mail address; and

a transmitter for directly transmitting image data to the image receiving apparatus by use of the IP address, the transmitter including a detector that detects whether or not a specific mark is added to the input destination data; and

~~wherein the memory stores the fixed address in association with a destination mail address;~~

~~an inputter for inputting the destination mail address; and~~

a searcher for searching the fixed address corresponding to the destination mail address input by the inputter, wherein the processor obtains the IP address of the image receiving apparatus by use of the fixed address searched by the searcher,

wherein the transmitter, in the first mode, directly transmits image data to the image receiving apparatus by use of the IP address in response to the IP address being obtained by the processor, and, in the second mode, indirectly transmits image data to the image receiving apparatus via a mail server in response to the IP address not being obtained by the processor,

wherein said transmitter directly transmits image data to the image receiving apparatus by use of the IP address when the specific mark is not added to the destination data, and indirectly transmits image data to the image receiving apparatus by use of the mail server when the specific mark is added to the destination data.

Claims 2-26 (Canceled)

27. (Currently Amended): An image transmitting apparatus for transmitting image data to an image receiving apparatus to which a changeable IP address is assigned by an external apparatus, the image transmitting apparatus transmitting the image data to an image receiving apparatus indirectly via a mail server, the image transmitting apparatus comprising:

a memory that stores a table including a plurality of fixed addresses each corresponding to one of a plurality of image receiving apparatuses, each fixed address being associated with destination data and comprising a MAC (Media Address Control) address;

an inputter that inputs destination data;

a searcher that searches the fixed addresses stored in said memory, and that obtains a fixed address corresponding to the destination data input by said inputter;

a processor configured to obtain a current IP address of an image receiving apparatus to which the image data is transmitted, by use of the fixed address obtained by said searcher; and

a transmitter configured to one of directly transmitting the image data to the image receiving apparatus by use of the IP address in response to the IP address being obtained by said processor and indirectly transmitting the image data to the image receiving apparatus via the mail server in response to the IP address not being obtained by the processor, the transmitter including a detector that detects whether or not a specific mark is added to the input destination data:

wherein said transmitter directly transmits image data to the image receiving apparatus by use of the IP address when the specific mark is not added to the destination data, and indirectly transmits image data to the image receiving apparatus by use of the mail server when the specific mark is added to the destination data.

28. (Previously Presented): The image transmitting apparatus according to claim 27, wherein the transmitter directly transmits the image data to the image receiving apparatus

P19203.A13

when the image transmitting apparatus and the image receiving apparatus are connected without requiring access to the Internet.

29. (Previously Presented): The image transmitting apparatus according to claim 27, wherein the image receiving apparatus comprises a personal computer connected to a network to which the image transmitting apparatus is connected.

30. (Previously Presented): The image transmitting apparatus according to claim 27, wherein the changeable IP address is assigned by a DHCP server.

31. (Previously Presented): The image transmitting apparatus according to claim 27, wherein said processor performs an RARP processing sequence to obtain the current IP address of an image receiving apparatus to which the image data is transmitted.

Claim 32 (Canceled)

33. (Currently Amended): The image transmitting apparatus according to claim [[32]] 27, wherein the specific mark comprises a @ mark.

34. (Currently Amended): An image transmitting apparatus for transmitting image data to an image receiving apparatus to which a changeable IP address is assigned by an external apparatus, the image transmitting apparatus transmitting the image data to an image receiving apparatus indirectly via a mail server, the image transmitting apparatus comprising:

a memory that stores a table including a plurality of fixed addresses each corresponding to one of a plurality of image receiving apparatuses, the fixed addresses comprising MAC (Media Access Control) addresses;

a processor configured to obtain a current IP address of an image receiving apparatus to which the image data is transmitted, by use of the fixed addresses stored in said memory; and

a transmitter that directly transmits the image data to the image receiving apparatus by use of the IP address obtained by said processor in response to the processor obtaining the IP address, the transmitter including a detector that detects whether or not a specific mark is added to the input destination data:

wherein said transmitter directly transmits image data to the image receiving apparatus by use of the IP address when the specific mark is not added to the destination data, and indirectly transmits image data to the image receiving apparatus by use of the mail server when the specific mark is added to the destination data.

35. (Previously Presented): The image transmitting apparatus according to claim 34, wherein said processor performs an RARP processing sequence to obtain the current IP address of an image receiving apparatus to which the image data is transmitted.

36. (Currently Amended): A method for transmitting image data to an image receiving apparatus to which a changeable IP address is assigned by an external apparatus,

P19203.A13

utilizing an image transmitting apparatus which indirectly transmits the image data to an image receiving apparatus via a mail server, the method comprising:

storing a plurality of fixed addresses each corresponding to one of a plurality of image receiving apparatuses into a memory, the fixed addresses being associated with a destination data and comprising MAC (Media Access Control) addresses;

inputting a destination address to which the image data is transmitted;

searching the fixed addresses stored in the memory, corresponding to the input destination address;

obtaining a current IP address of an image receiving apparatus to which the image data is transmitted, by use of the fixed address; and

directly transmitting the image data to the image receiving apparatus by use of the obtained IP address in response to an IP address being obtained,

wherein the direct transmitting includes detecting whether or not a specific mark is added to the input destination address; and

wherein the direct transmitting of image data to the image receiving apparatus by use of the IP address is performed when the specific mark is not added to the destination address;

and

indirectly transmitting image data to the image receiving apparatus by use of the mail server is performed when the specific mark is added to the destination address.

37. (Previously Presented): The method according to claim 36, wherein an RARP processing sequence is performed to obtain the current IP address of an image receiving apparatus to which the image data is transmitted.

Claim 38 (Canceled)

39. (Currently Amended): A method for transmitting image data to an image receiving apparatus to which a changeable IP address is assigned by an external apparatus, utilizing an image transmitting apparatus which indirectly transmits the image data to an image receiving apparatus via a mail server, the method comprising:

storing a plurality of fixed addresses each corresponding to one of a plurality of receiving apparatuses into a memory, each fixed address comprising a MAC (Media Access Control) address;

obtaining a current IP address of an image receiving apparatus to which the image data is transmitted, by use of the fixed addresses stored in the memory; and

directly transmitting the image data to the image receiving apparatus by use of the obtained IP address in response to obtaining an IP address,

wherein the direct transmitting includes detecting whether or not a specific mark is added to the input destination address;

P19203.A13

wherein the directly transmitting of image data to the image receiving apparatus by use of the IP address is performed when the specific mark is not added to the destination address; and

indirectly transmitting of image data to the image receiving apparatus by use of the mail server is performed when the specific mark is added to the destination address.

40. (Previously Presented): The method according to claim 39, wherein an RARP processing sequence is performed to obtain the current IP address of an image receiving apparatus to which the image data is transmitted.